




Novostrip SP



Profile made of extruded aluminium intended to be installed in stairs, ramps or passage areas with marble, terrazzo or similar floorings, to guarantee safety against eventual falls.


This profile is easy to install on finished floorings, it will be enough by applying adhesive. Due to its geometry, it's ideal for installing it in any environment, specially in old areas which need a better safety transit in already tiled stairs. Thanks to its tiny design, can be integrated on the flooring. Available in matt silver, matt black and champagne finishes, colors wich perfectly fits with the latest trends.

Applications


Profile made of anodized aluminum with striated visible side.

Its main function is a an anti-slip solution in stairs or ramps made of marble, granite, ceramics, concrete, etc

General Features



Material:	Anodized aluminum
Length:	2,5 ml
Dimensions:	a: 12 mm. h: 2,5 mm.
Packaging:	50 u/box
Finishes:	



Plata mate - 13



Negro mate - 90



Champagne - 166

Technical Features and tests

Alloy	6063 L-3441	AA y ASTM UNE 38-301-89
Fire resistance	M0	UNE 23-727-90
Abrasion resistance	Very good	
Lightfastness	Excellent	
Appearance and color	EN 12373-1	
Slip resistance	Good	UNE-ENV 12633:2003

Materials

Novostrip SP is a profile made by aluminum extrusion. The anodizing process improves the corrosion resistance, mechanical resistance and appearance of profiles. It has the quality seal Qualanod, which guarantees the quality of the process and the resulting profiles. This seal regulates several tests: appearance and color, thickness measurements, sealing and impregnation control, abrasion resistance, lightfastness, acetic saline chamber and nitric acid immersion.

Aluminum is a material with excellent chemical, physical and mechanical properties. It is lightweight, tough, ductile, malleable and highly durable.

Installation

Novostrip SP is easy to install.

Limpie las superficies a unir para garantizar una perfecta adhesión. Clean the surfaces to join to guarantee a perfect adhesion. Spread a big amount of adhesive on the rear side of Novostrip SP, place the profile on the desired surface and press carefully. Finally let the adhesive dry.

You can repeat the installation to install as many profiles as you need, creating your own pattern.

Cleaning and maintenance

Novostrip SP resists water and detergents. The cleaning must be done periodically with a soft cloth. If you use a neutral liquid cleaner, you must rinse the profile with cold water and dry to remove excess moisture. If dirtiness persists, clean the profile with a solution with clean water and detergent or neutral soap 5%, brushing with a cloth with no particles that could scratch the finish. Outdoors, rainfall will clean the profile.

Steel wool, abrasive cleaners, souring products as well as strong acids (hydrochloric and perchloric), strong bases (caustic soda or ammonia) or carbonated solutions are not recommended. Citric acid is neither recommended because it dissolves the protective layer of the surface of aluminium. Waxes, petrolatum, lanolin or similar substances are not appropriate. Solvents containing haloalkanes (hydrofluoroether and chlorinated solvents) and curing accelerators containing chlorides should not be used (use special accelerators free of chlorides).

Technical information

You can find out more information about the technical features of the Emac®'s products by downloading its Technical Files in www.emac.es.

If you have any query, please contact our Technical Department in tecnico@emac.es



Emac Complementos S.L. (Spain) info@emac.es // Emac America L.L.C. (FL,USA) info@emac-america.com // Emac Italia S.R.L. (Italy) info@emac-italia.it
www.emac.es

*The data provided are for information only and have been obtained by our supplier or Emac®.
Does not constitute legal guarantee in terms of properties and / or functionality of the application of material*